


RODIM PAINT PROTECTION FILMS
Installations After Care

RODIM[®]





INSTALLATION AFTERCARE: How long does PPF take to cure?

- The application fluid applied during the installation of Rodim PPF may need some time to dry. This drying period can be longer in cold or cloudy weather and shorter in warm weather or with direct sunlight. You may observe small water droplets and a slightly cloudy appearance while the film dries. Since the film will eventually dry fully, a slower drying time should not be a cause for concern. The film needs 30 days to cure fully. The car needs to be sent to the detailing studio for maintenance check for decontamination every 6 months & its records to be maintained by customers.
- Right after installation, there may be a small amount of setting solution trapped under the film. This is completely normal and will dissipate within a short time (up to a week, depending on weather conditions).
- Avoid pressing on the area where the solution is present. The appearance will resemble the temporary blemishes seen during Paint Protection film installation, such as streaking or watery bubbles. This is part of the curing process, and these visual imperfections will clear up in few days. Minor variations in the material itself will also resolve over time with exposure to the elements. Some cosmetic imperfections are unavoidable and may become noticeable due to the installation method used for the film. Installation related issues if any would be taken care by the detailing studio.

How do you maintain PPF ? :



- After film installation, wait one week before washing or waxing your vehicle to help ensure proper adhesion build of the film has been achieved.
- Please return to the shop for Re - checking of PPF Installation after one week of installation..(Its very much recommended) 
- After washing your car, use a clean microfiber towel to dry it. Although PPF requires special care, its maintenance is much easier if compared to the maintenance of an unprotected car-exterior. 
- Do not wipe or scrub the film in direct sunlight or when the film is hot.
- Do not use dyed or coloured car waxes on the film.
- Do not use aggressive force or aggressive chemicals.
- Do not use solvent-based degreasers.
- Remove any wax build-up along film edges with a lint-free cloth.
- Don't use a powered polishing equipment / polisher / Sander on the PPF , wax can be applied by hand application only.
- Do not use high-pressure water hoses to wash car at the edges.
- Don't use a lot of pressure on the film when cleaning.
- Don't use body covers over PPF cars as it may damage or transfer its colour to the PPF.
- Water marks caused by hard water / acidic rains etc / Birds Dropping / Tree Sap– which if left to dry on the paint protection film for longer time may leave a stain.

How to wash my car after PPF Installation?

1. Wash your vehicle regularly. 
2. Don't wash your vehicle in direct sunlight or while the exterior surface is hot. 
3. Use premium washing products. Use clean Microfibre Cloth to mop the car.
4. Use pH neutral car wash product. Other acidic or caustic cleaning media can damage the product.
5. Always wash cars from top to bottom , Use separate clean microfibre cloths to clean car body , glasses & alloys.
(Change them regularly in few weeks once they become coarse & hard , needs to be washed daily after cleaning the car)
6. Rinse your vehicle thoroughly before applying shampoo or mopping in dusty / muddy condition.
7. Don't let your vehicle air-dry. Always wipe it clean using a high absorbent Microfibre Cloth before the water dries or else it can leave water marks on the car.
8. Avoid going to an automated car wash as their bristles can damage the PPF edges.
9. It is recommended to carry out deep care , decontamination and maintenance on the PPF every six months, and it is not recommended to polish the surface where PPF is installed ;

Installation Quality Assurance : Our team should take full liability for the vehicle's OEM paint during the PPF application. Any damage caused during this phase should be professionally repaired at no cost to the client.

Warranty Assessment: Throughout the warranty period, we stand behind our work. If the paint is impacted due to our PPF application, We should address the issue. To ensure an accurate resolution, a professional assessment should be conducted to determine if the impact resulted from the film or external factors such as accidental damage or any external issues .

Warranty Repairs for paint : To ensure the highest quality of repair and maintain customer vehicle's standards, all paint restoration work should be carried out exclusively at reliable good Paint Shop.

Exclusion for Repainted Panels: Liability coverage is limited to original factory painted panels. The installation partner will not be responsible for paint damages occurring on panels that were repainted before the PPF application.

RODIM[®]

A brand of BASF - We create chemistry



Thanks